





RD..A type pressure reducing valves - 3 way

- Direct acting
- With relieving
- Spool type
- From SAE08 to SAE10 cavities

Technical specifications and diagrams are measured with mineral oil of 46 cSt viscosity at 40°C (104°F) temperature.

		RD08A	RD10A
Nominal flow		8 l/min (2.1 US gpm)	30 l/min (7.9 US gpm)
Max. pressure			line 1=150 bar (2175 psi) line 2=350 bar (5100 psi)
Oil leakage	at 100 bar (1450 psi)	10 cm ³ /min (0.61 in ³ /min)	40 cm ³ /min (2.44 in ³ /min)
Fluid		mineral based oil	
Viscosity		10-200 cSt	
Max level of contamination		20/18/14 ISO4406	
Fluid temperature	with NBR seals with FPM seals	from -20°C (-4°F) to 80°C (176°F) from -20°C (-4°F) to 100°C (212°F)	
Environmental temp. for working conditions		from -20°C (-4°F) to 50°C (122°F)	
Cavity		SAE 08/3	SAE 10/3
Weight		0.240 kg (0.53 lb)	0.360 kg (0.79 lb)

NOTE - For different conditions, please contact Walvoil Sales Dpt.




Valve type	A		B		C	D	Nm	lbft
	mm	in	mm	in				
RD08A/OS	40.8	1.60	79.5	3.13	24	24	30	22
RD10A/OS	47.2	1.86	94.5	3.72	27	27	50	37

For dimensions with different type of adjustment see page 212

Ordering codes and description composition

RD08A/OS2B



1 Cartridges

TYPE	CODE	DESCRIPTION
SAE cavity 08/3		
RD08A/OS1B	ORD08002003	Screw adjustment, pressure range 1
RD08A/OS2B	ORD08002005	Screw adjustment, pressure range 2
RD08A/OS3B	ORD08002000	Screw adjustment, pressure range 3
SAE cavity 10/3		
RD10A/OS1B	ORD10002003	Screw adjustment, pressure range 1
RD10A/OS2B	ORD10002001	Screw adjustment, pressure range 2
RD10A/OS3B	ORD10002000	Screw adjustment, pressure range 3

2 Adjustments

TYPE	DESCRIPTION
S	Screw
V	With handwheel see point 7

3 Pressure range

Standard setting is referred to at 5 l/min (1.32 US gpm) flow

TYPE	DESCRIPTION
1	Pressure range 5÷50 bar (72.5÷725 psi); Std. setting 30 bar (435 psi)
2	Pressure range 20÷100 bar (290÷1450 psi); Std. setting 50 bar (725 psi)
3	Pressure range 50÷150 bar (725÷2175 psi); Std. setting 100 bar (1450 psi)

4 Seals

TYPE	DESCRIPTION
B	NBR (Buna) o-ring seals, std configuration
V	FPM (Viton) o-ring seals, contact Sales Dept.

5 Valve body

TYPE	CODE	DESCRIPTION
SAE 08/3-G 1/4	3CC0830B11	Aluminium body for cavity 08 valve, G 1/4 std thread
SAE 10/3-G 3/8	3CC1030C11	Aluminium body for cavity 10 valve, G 3/8 std thread

Note: aluminium body can stand up to 210 bar (3050 psi)
For steel bodies or different threading see page 217

6 Springs


TYPE	CODE	DESCRIPTION
SAE cavity 08/3		
1	3ML1103600	Pressure range 1 - no band
2	3ML1103601	Pressure range 2 - no band
3	3ML1104000	Pressure range 3 - no band
SAE cavity 10/3		
1	3ML1144601	Pressure range 1 - green band
2	3ML1144602	Pressure range 2 - blue band
3	3ML1144603	Pressure range 3 - red band

7 Accessories

TYPE	CODE	DESCRIPTION
-	4VL2407100	handwheel

Rating diagrams

RD08A reducing/relieving pressure vs. flow



RD10A reducing/relieving pressure vs. flow

